

美制锯齿螺纹 American Buttress

类型 Type	型号 Designation 右手 (right)	SMX30	SMX50	型号 Designation 左手 (left)	SMX30	SMX50	TPI	尺寸 Dimensions(mm)				图片 Picture
								d	l	x	f	
外螺纹 Extrnal	16ER-16BBUT			16EL-16BBUT			16	9.525	16	1.1	1.6	
	16ER-12BBUT			16EL-12BBUT			12	9.525	16	1.4	2.1	
	16ER-10BBUT			16EL-10BBUT			10	9.525	16	1.4	2.2	
	16ER-8BBUT			16EL-8BBUT			8	9.525	16	1.6	2.5	
	22ER-8BBUT			22EL-8BBUT			8	12.7	22	1.6	2.5	
内螺纹 Internal	16IR-16BBUT			16IL-16BBUT			16	9.525	16	1.1	1.6	
	16IR-12BBUT			16IL-12BBUT			12	9.525	16	1.4	2.1	
	16IR-10BBUT			16IL-10BBUT			10	9.525	16	1.4	2.2	
	16IR-8BBUT			16IL-8BBUT			8	9.525	16	1.6	2.5	
	22IR-8BBUT			22IL-8BBUT			8	12.7	22	1.6	2.5	

立式车螺纹刀片 Vertical threading inserts

类型 Type	型号 Designation 右手 (right)	SMX30	SMX50	型号 Designation 左手 (left)	SMX30	SMX50	螺距 (mm)	TPI	尺寸 Dimensions(mm)			图片 Picture
									d	l	x	
不完全修光刃50°	16VER-A60	○	○	16VEL-A60			0.5~1.5	48~16	9.525	16	0.9	
	16VER-G60	●	●	16VEL-G60			1.75~3.0	14~8	9.525	16	1.7	
	16VER-AG60	●	●	16VEL-AG60			0.5~3.0	48~8	9.525	16	1.7	
	22VER-G60	○	○	22VEL-G60			1.75~3.0	14~8	12.7	22	2.5	
	22VER-N60	●	●	22VEL-N60			3.5~5.0	7~5	12.7	22	2.5	
不完全修光刃55°	16VER-A55	○	○	16VEL-A55			0.5~1.5	48~16	9.525	16	0.9	
	16VER-G55	●	●	16VEL-G55			1.75~3.0	14~8	9.525	16	1.7	
	16VER-AG55	●	●	16VEL-AG55			0.5~3.0	48~8	9.525	16	1.7	
	22VER-G55	○	○	22VEL-G55			1.75~3.0	14~8	12.7	22	2.5	
	22VER-N55	●	●	22VEL-N55			3.5~5.0	7~5	12.7	22	2.5	

JTGR 立装外切槽用 JTGR Vertical external groove

图片 Picture	刀片型号	尺寸 Dimensions(mm)			SMX30		SMX50	
		W=0.08	φd	S	R	L	R	L
	JTGR/L3100	1.00	9.525	3.97	●		●	
	JTGR/L3115	1.15			○		○	
	JTGR/L3120	1.20			●		●	
	JTGR/L3135	1.35			○		○	
	JTGR/L3150	1.50			●		●	
	JTGR/L3165	1.65			●		●	
	JTGR/L3175	1.75			●		●	
	JTGR/L3195	1.95			○		○	
	JTGR/L3200	2.00			●		●	
	JTGR/L3220	2.20			●		●	
	JTGR/L3250	2.50			●		●	
	JTGR/L3265	2.65			●		●	
	JTGR/L3300	3.00			●		●	

●: 库存项 ○: 准库存
●: Stock item ○: Underpring forstoc